

A semantic-web oriented representation of the clinical element model for secondary use of electronic health records data

Cui Tao,¹ Guoqian Jiang,¹ Thomas A Oniki,² Robert R Freimuth,¹ Qian Zhu,¹ Deepak Sharma,¹ Jyotishman Pathak,¹ Stanley M Huff,² Christopher G Chute¹

► Additional material is published online only. To view please visit the journal online (<http://dx.doi.org/10.1136/amiajnl-2012-001326>).

¹Biomedical Statistics and Informatics, Mayo Clinic, Rochester, Minnesota, USA
²Intermountain Healthcare, Salt Lake City, Utah, USA

Correspondence to

Dr Cui Tao, Department of Health Sciences Research, Mayo Clinic, 200 First Street SW, Rochester, MN 55905, USA;
tao.cui@mayo.edu

Received 10 September 2012

Revised 22 November 2012

Accepted 2 December 2012

Published Online First

25 December 2012

ABSTRACT

The clinical element model (CEM) is an information model designed for representing clinical information in electronic health records (EHR) systems across organizations. The current representation of CEMs does not support formal semantic definitions and therefore it is not possible to perform reasoning and consistency checking on derived models. This paper introduces our efforts to represent the CEM specification using the Web Ontology Language (OWL). The CEM-OWL representation connects the CEM content with the Semantic Web environment, which provides authoring, reasoning, and querying tools. This work may also facilitate the harmonization of the CEMs with domain knowledge represented in terminology models as well as other clinical information models such as the openEHR archetype model. We have created the CEM-OWL meta ontology based on the CEM specification. A convertor has been implemented in Java to automatically translate detailed CEMs from XML to OWL. A panel evaluation has been conducted, and the results show that the OWL modeling can faithfully represent the CEM specification and represent patient data.

INTRODUCTION

Background

Healthcare system interoperability is one of the most important goals for meaningful use of the electronic health records (EHR). It is essential to facilitate IT support for workflow management, decision support systems, and evidence-based healthcare, as well as secondary use of EHR across healthcare organizations. The clinical element model (CEM)^{1,2} was designed to provide a consistent architecture for representing clinical information in EHR systems. The CEM has been adopted in the Strategic Health IT Advanced Research Project, secondary use of EHR (SHARPn)³ as the common unified information model for unambiguous data representation, interpretation, and exchange within and across heterogeneous sources and applications.

The current CEM was represented either in the Clinical Element Modeling Language (CEML), an XML-based language for expressing the structure and constraints of CEM models;⁴ or in the Constraint Definition Language (CDL),¹ which defines a superset of CEML functionality, with extensions including additions of new constraints to the modeling language, formalization of the model specialization capabilities, and a concrete reference object model. Although CDL brings more formalization to the CEM definition, neither CDL nor CEML currently

supports inferences or rules, which are critical to add computerized support and reasoning to the CEM models and populated patient data. In addition, there is no open-source tooling available yet to support CDL authoring or querying, and there is a lack of tooling for automatic consistency checking or reasoning for the CEM.

Proposed solution and impact

One way to integrate CEMs with the above functionalities is to translate CEM definitions to an ontology language. In this project, we chose to use the Web Ontology Language (OWL),⁵ which we believe serves best for our purpose for the following reasons. OWL is built on formalisms that use description logic (DL)⁶ to allow reasoning and inference. The rule interchange format (RIF)⁷ can be used to add rules to OWL and can be used to infer new knowledge from an OWL based ontology and reason about OWL individuals. Moreover, the Semantic Web community has developed open source tools for editing, storing, and reasoning over information represented in OWL. The vast ongoing supports and investments on OWL and its related tools make it very valuable to align clinical information model languages such as CEML, CDL, and Archetype Definition Language (ADL)⁸ to OWL, so that the OWL-related tools can be directly applied to these models.

The OWL representation also provides an environment to seamlessly integrate information models and terminology models used in the clinical context. The CEM is an information model that represents the logical structure of data within an EHR. Information models usually connect to terminologies (eg, SNOMED CT⁹ for clinical terms, RxNorm¹⁰ for medications), which define the domain knowledge of concepts used in the information model. Unfortunately, information models and terminology models are usually developed by different groups and are expressed in very different syntaxes, which complicates the efforts to interface the information expressed in the models.¹¹ OWL and Semantic Web technologies have already been applied in representing and validating many terminology models.^{12–16} If the CEM can be represented in OWL, the information model (CEM) and terminology models can be represented in the same language and representation environment, thereby facilitating the integration of information and terminology models.

In addition, an OWL representation of the CEM can potentially facilitate the harmonization and

To cite: Tao C, Jiang G, Oniki TA, et al. *J Am Med Inform Assoc* 2013;**20**:554–562.

Table 1 Basic clinical element model (CEM) categories

Category	Definition	Example
Statement	A complete assertion about a particular aspect, a characteristic or condition of a patient	<i>DiastolicBloodPressureMeas</i> : a single statement model, where it captures the value of the DBP measurement
Panel	A common grouping of clinical observations. It is a collection of other statements or panels	<i>BloodPressurePanel</i> can contain items such as <i>DiastolicBloodPressure</i> and <i>SystolicBloodPressure</i>
Component	Is similar to a statement in CEM, except that it cannot be persisted alone in the EHR, but must be persisted as an internal part of another model with type such as Statement or Panel	
Attribution	Declares the who, where, why, and when information regarding an action	The model <i>BloodPressurePanel</i> has an attribution called 'Observed', which describes when, who, where, and why the blood pressure measurement was obtained
Qualifiers	Is used to add useful information to an instance but does not change the meaning of the data or items of the instance	<i>BodyPosition</i> of <i>HeartRateMeas</i> is a qualifier. In this case, whether the patient was sitting or standing during the measurement does not affect the meaning of the measurement itself
Modifier	Alters the meaning of the instance	<i>Subject</i> of model <i>HeartRateMeas</i> is a modifier. In this model, the subject changes the semantic interpretation of the measurement

DBP, diastolic blood pressure; EHR, electronic health records.

between a CEM element and its associated statements/panels, components, qualifiers, modifiers, or attributions respectively. For example, the OWL class *BloodPressurePanel* has two sub-statements associated with the *item* property: *SystolicBloodPressureMeas* and *DiastolicBloodPressureMeas*. In addition, the OWL object property *data* is used to define any values for a CEM statement or component. For example, we can declare the actual value of a patient's systolic blood pressure measurement using the *data* property. The detailed description of how we defined these basic categories and relations has been discussed previously.¹⁸

Category classes associations

The basic category classes can be used to represent individual clinical elements. Sometimes there is also a need to represent associations among the defined clinical elements. For example, the information of a particular patient could be stored in one statement instance while the information of the patient's family members could be stored in other statement instances. In this case, we must define the relation between two patient statement instances and annotate the relation as Parent-Child. In this section, we discuss how to define different types of associations among categories using the *Association* specification in CEM.

An *association* is used to represent a collection of related statements, components, qualifiers, modifiers, and/or attributions. An association is bound with a vocabulary concept that defines its semantic meaning. Associations may be specialized as *panels*, *collections*, *sequences*, *lists*, *semantic links*, and *annotations*.

A *collection* or a *panel* is an association that references a set of associations and/or statements. The primary difference between the two is that a panel represents a very strong relationship between its embedded elements, whereas a collection represents a weak relationship. For example, we could use a blood pressure panel association to represent the systolic and diastolic blood pressure (DBP) observations taken together. In contrast, a collection may be arbitrarily defined and reference associations and/or statements that share limited context. In the OWL representation, we created new OWL classes for *collection* and *panel*, where the semantic definition for both classes is that they can only associate either associations or statements through the *item* property.

We can also define a sequence of a set of clinical elements. We adopted the OWL sequence extension¹⁹ to express a sequence in OWL vocabulary, which is supported by DL reasoners.¹ The OWL sequence extension introduces the *OWList* class to define a member in a sequence. The *hasNext* property points to the next member in the sequence and the content of the member is associated using the *hasContents* property. Figure 2 shows an example of how to use the OWL sequence extension to represent a CEM sequence about the use of a catheter in a patient. In that example, a CEM statement describes the insertion of the catheter, statements describe site maintenance, and a statement describes the removal of the catheter.


In CEM, a *list* is an association that contains a set of references of some other independent statements or associations. We define a new class called *List* in CEM-OWL. Since the order of referenced elements in the list is not significantly important, we propose the use of *owl:unionOf* to represent the association of a list. The List class itself is the union of the referenced statements and/or associations.

A *semantic link* is an association that represents a strong semantic relationship between two or more statements/associations. Statements and/or associations referenced in a semantic link are assumed to serve some role in the semantic link. For example, a semantic link can be used to represent the relationship between a diagnosis statement and a medication administration statement indicating that the medication was administered to treat the diagnosis condition, or the relationship between the subjects of two patient statements is Parent-Child. Figure 3A shows an example of how a semantic link could be represented in OWL. In the example, the class *Treatment* is a semantic link that references two statements *Diagnosis* and *Med_admin* and the definition includes 'a treatment must treat some diagnosis with some medication'.

In CEM, an *annotation* is an association that adds independent textual annotation information to the referenced statements

¹RDF provides classes such as *rdf:list* and *rdf:seq* to represent a collection of items. Although the *rdf:seq* class is the RDF 'Sequence' container, by convention it is used to indicate to human readers that the order of contained items is intended to be significant. There are no logical semantics defined to a DL classifier in a *rdf:seq*. In addition, RDF vocabulary such as *rdf:list* cannot be used in OWL-DL¹⁸.

Figure 2 Example of representing sequence using Web Ontology Language list.



and/or associations. For example, a clinician can comment on observation such as laboratory results. Figure 3B shows an example of how we represent a CEM annotation in OWL. The class *Clinician_Lab_Result_Comparison_Comment* is a subclass of *Annotation* that references two statement classes, which must be lab result observations. A textual annotation value can be appended as an OWL Annotation Property to the *Annotation* class to store any comments to this annotation.

DETAILED MODEL REPRESENTATION

The CEM-OWL meta-ontology described above can be used to represent each detailed CEM in OWL. The representation of a detailed CEM has constraints on the values that can be legally stored in a particular element. A constraint can (1) limit an element to contain instances of a specific reference class (eg, qualifier, modifier, attribution), (2) limit the data contained in the element to that described by a specific model (eg, a body position model), (3) define the cardinalities, and (4) restrict the domain from which data values in the element are derived (eg, a value set).

To limit an element to contain instances of a specific reference class, any detailed CEM that belongs to a category should be declared as a subclass of the corresponding category class (figure 4, reference point 1). It therefore inherits all the semantic definitions of its parent classes. Figure 4 shows an example of how we represent the *BloodPressurePanel* model. Figure 4A shows the *BloodPressurePanel* model in the CDL format and figure 4B shows its OWL representation (partial).ⁱⁱ Since CDL defines that *BloodPressurePanel* is a *Panel*, we define the class *BloodPressurePanel* to be a subclass of the *Panel* class so that it inherits the semantic definition of the *Panel* class (see figure 4, reference point 2).

To limit the data contained in the element to that described by a specific model, we can link the referenced elements in each detailed CEM using the properties *item*, *qual*, *mod*, and *att*. Figure 4A lists a set of items, qualifiers, attributions, and one modifier. As figure 4B, reference point 1 shows, we can define that the *BloodPressurePanel* class has items *DiastolicBloodPressureMeas* and *SystolicBloodPressureMeas*, attribution (via *att*) *Observed*, modifier (via *mod*) *Subject*, *qualifier* (via *qual*) *BloodPressureBodyLocationPrecoord*, etc.

CDL defines cardinality constraints of each embedded CEM. OWL provides three constructs for cardinality constraints: *owl:cardinality*, *owl:minCardinality*, and *owl:maxCardinality*. These constraints can be used to faithfully represent the cardinality constraints defined by CDL. As figure 4B reference point 1

shows, we can define that each blood pressure panel can only have maximally one item referencing *DiastolicBloodPressure* using *owl:maxCardinality*.

In CEM, a value set is a category of like concepts. A value set constrains the permissible values of a particular value domain. For example, figure 4A shows two such constraints for Blood Pressure Measurement Device and Blood Pressure Body Location. In CEM-OWL, we define a value set following the guideline proposed by the W3C.²⁰ The W3C guideline proposes two options to represent a value set: representing values in a value set as individuals or as subclasses. Here we follow the second approach,ⁱⁱⁱ where each value set is presented as an OWL class and the features of the class represent a space that is partitioned by the values (ie, permissible values) in the value set. Each permissible value in the value set is represented as individual OWL classes, and defined as subclasses of the OWL class for the value set itself. These individual classes are defined as disjoint to each other, and the value set is defined as an exhaustive union of its permissible value classes. In figure 4B, reference point 4, for example, the class *BloodPressureBodyLocationPrecoord* represents a value set with three permissible values: *Arm*, *Finger*, and *Wrist*, each of which is a subclasses of the *BloodPressureBodyLocationPrecoord* class and is disjoint from the other two. In addition, the class *BloodPressureBodyLocationPrecoord* is defined as an exhaustive union of the three subclasses. This way we can restrict the values for blood pressure body location to only these three choices.

We also propose how to represent units of measure defined in CEMs. In order to ensure semantic interoperability, we adopted the Measurement Unit Ontology (MUO)²¹ and the Unified Code for Units of Measure (UCUM).²² For each physical quality data value we define a new class that is a subclass of the *QualityValue*^{iv} class in MUO. We can then use the MUO property *measuredIn* to define the allowed units of this quantity value. In the example in figure 4B, reference point 3, we defined that each *DiastolicBloodPressure* can have at most one *DiastolicBloodPressureData*, which is defined as a subclass of *MUO:QualityValue* (figure 4B, reference point 6). A *DiastolicBloodPressureData* can only be measured in terms of a *PressureUnit* (figure 4B, reference point 6), which is a value set that contains all of the pressure units that are defined in UCUM. We can also use the MUO property *Preferred Unit* to define the preferred unit (*MilliMetersOfMercury*) for this quantity value (figure 4B, reference point 5).

ⁱⁱDue to space limitation, here we only show partial OWL representation of the *BloodPressurePanel* model for the purpose of illustrating how we represent detailed CEMs by adding different constraints.

ⁱⁱⁱThe choice between one and the other is based on each individual case, and is not within the scope of this paper.

^{iv}This is how MUO named this class to represent the value of an individual quality, for instance the weight of an individual object.




Figure 3 Examples of Semantic Link (A) and Annotation (B).

USE CASE ILLUSTRATION

After the semantic representation of the CEMs as well as the populated CEM patient data, Semantic Web technologies can be used to perform consistency

checking, automatic classification, and automatic inference by linking to existing domain ontologies. In this section, we use a few use cases to illustrate the above semantic functionalities.





Figure 4 Example representation of a detailed clinical element model in Constraint Definition Language (CDL) and Web Ontology Language: (A) the CDL representation of the blood pressure panel model; (B) the Web Ontology Language representation of the blood pressure panel model (partial).

Figure 5 Examples with inconsistencies: (A) model inconsistency; (B) value set inconsistency.



Consistency checking

We can perform consistency checking on both the model level and the instance level. On the model level, since the meta-ontology semantically defines the basic category class, any detailed CEM must follow the restriction defined. Figure 5A shows an example. As the bottom part of figure 5A shows, a panel is defined to associate with either associations or statements as its item. If a CEM modeler decided to create a new Panel that has at least one component as its item (rather than an Association or a Statement), a semantic reasoner will return an error due to this inconsistency. This illustrates how the OWL representation of the CEM meta-model can be used to ensure the correct implementation of detailed CEMs.

On the instance level, we can check if a particular instance has the correct number of linked components as defined by the cardinality constraints, or has a value within the correct data ranges and with appropriate units of measurement, or has appropriate values as defined by the specific value sets. Figure 5B shows an example of value inconsistency. The blood pressure body location has been defined as arm, finger, or wrist, as the upper part of figure 5B shows. The lower part of figure 5B shows sample data with the blood pressure body location as leg, which is not an instance of arm, finger, or wrist. In this case, a reasoner will return an error due to this inconsistency.

Automatic classification

We can semantically define a class using OWL equivalent classes and axioms. Then a semantic reasoner can automatically determine whether an individual belongs to the class. Figure 6 shows an example. We can define that normal DBP data must be within a particular range as the upper part of figure 6 shows. The lower part of figure 6 shows two sample DBP data values: one is 120 and the other one is 65. As we can see the system automatically classified the second one as a *NormalDBPData*, but not the first one. Similarly, we can define other classes using OWL DL.

Semantic reasoning

The CEM-OWL representation can also provide a more natural connection to existing ontologies and semantic technologies. EHR data representations, such as CEMs, need to reference domain ontologies such as SNOMED CT, RxNorm, and LOINC, for the semantic meaning of each element. OWL can serve as a common platform to link information models such as CEM to the domain ontologies. In addition, the populated patient data with respect to the CEM-OWL makes it easier for us to leverage existing Semantic Web based tools to further semantic reasoning.

Here we use one example in figure 7 to illustrate how CEM-OWL, domain ontologies, and semantic reasoners need to

be used together to infer information for a phenotyping algorithm. The upper part of figure 7 shows one of the conditions a patient must qualify to be classified as a resistant hypertension patient. The lower part of figure 7 shows a few sample sentences from a patient’s clinical notes. We want to semantically represent the patient’s medication history and blood pressure measurement history in a structured way using CEM. More specifically we can use the *SecondaryUseNotedDrug* class to represent medication information and the *BloodPressurePanel* class to represent the values of systolic blood pressure measurements and DBP measurements, as well as the patient location (inpatient or outpatient). As we discussed above, each detailed CEM has a key that links to its corresponding concept in a domain ontology. Labetalol 100 mg, for example, can be linked to SNOMED CT concept SCT318445000. Based on SNOMED-CT, the system can infer that ‘labetalol 100 mg’ (SCT318445000) is an antihypertensive drug (SCT1182007). In addition, we can leverage existing Semantic Web tooling to perform reasoning after representing the patient data with respect to the CEM-OWL. For example, we can use the Clinical Narrative Temporal Relation Ontology (CNTRO)²³ and its associated temporal-relation reasoning framework to handle time aspects in this query. As this simple example illustrates, retrieving answers to clinically important queries usually involves comprehensive inference processes.

IMPLEMENTATION RESULTS AND EVALUATION

CEM-OWL evaluation

We have created the CEM-OWL meta-ontology based on the CEM specification.¹ A convertor has been implemented in Java




Figure 6 An example of automatic classification.

Figure 7 Conditions and sample patient data for resistant hypertension.

Conditions a patient must qualify to be classified as Resistant Hypertension patient:

Has two outpatient measurements of SBP > 140 or DBP > 90 at least one month after taking anti-hypertensive drugs.

Sample sentences from a patient's clinical records:

Patient was put on Labetalol 100mg from Mar 1st.
 Follow-up BP in 5 weeks: SBP=156, DBP=110
 Today's BP measurements: SBP=148, DBP=112 (note date: May 1)

to automatically translate all the detailed CEMs from XML to OWL, which was used to covert all the 183 detailed CEMs for SHARPN to OWL.

We followed the ontology evaluation criteria introduced by Brank *et al*²⁴ to evaluate the CEM-OWL modeling. The ontology evaluation criteria cover several levels: syntactic, lexical, hierarchical, semantic relations, and context and application. The OWL ontology has been validated using HerMiT reasoner V0.8.1 embedded in Protégé 4.1 (<http://protege.stanford.edu>) for syntactic and consistency checking. For other evaluation criteria, a review panel with two CEM experts (TAO and TC) and one OWL expert (GJ) conducted manual evaluations followed by extensive discussions. The members of the review panel are independent of the development of the CEM-OWL model. Each reviewer used a scoring system from 1 to 5 (strongly disagree, disagree, unable to assess, agree, strongly agree) to evaluate the ontological representation for each criterion. After evaluating each criterion, the reviewers compared and discussed their scores until agreement was reached on a single score. We considered a score of 4 or 5 to indicate that the OWL representation was satisfactory and could faithfully represent the original intended meaning of the CDL specification.

Table 2 shows the evaluation results. The review panel assigned a score 5 (strongly agree) to five out of the seven evaluation criteria and a score 4 (agree) to the remaining two evaluation criteria. For the two criteria with a score 4, justifications are provided in the comments column.

From the evaluation results, we can conclude that the lexical and semantic definitions of the classes, the hierarchical structure, as well as the semantic relation definitions in the meta-ontology are well defined and can faithfully represent the CEM specification. For the context and application criterion,

we evaluated the usage of the classes, relations, and cardinality constraints on a detailed CEM (*BloodPressurePanel*). The review panel agreed that those components were sufficient to faithfully represent the semantic meaning of the detailed CEM model and the detailed CEM model was represented correctly using these components in OWL. Please note that we did not include the usage of value set definition and unit of measurement definition in the evaluation because neither is included in the CDL specification and therefore they are not included as part of the meta-model. This will be included in a future project on data type definition.

OWL convertor evaluation

The evaluation of the automatic detailed CEM convertor contains two steps. The first step is a manual comparison between the automatic generated OWL files and the corresponding original XML file. Three experts (RRF, QZ, and FC, who are independent of the CEM-OWL model development as well as the CEM-OWL converter implementation) evaluated different aspects of the converted OWL files including name spaces, class and property naming conventions, domains and ranges, class hierarchies, cardinality constraints, and relation definitions. All experts have agreed that the converted files can faithfully represent the original contents.

The second step is to test the usage of these converted OWL files. In order to do this, we have represented the medication and demographic information of 400 patients from the SHARPN normalization pipeline in RDF using the CEM-OWL ontologies. The patient data have been successfully represented in RDF. We can therefore conclude that the CEM-OWL ontologies we designed are capable of representing real patient data.

Table 2 Clinical element model (CEM)-Web Ontology Language (OWL) representation evaluation result

Criterion	Score	Comments
Definition of classes (lexical)	5	The reviewers agreed that the lexical definition of each class is clear
Hierarchical structure (sub-classes hierarchy)	4	The reviewers agreed that the sub-class hierarchy faithfully represents the CEM specifications. There is a concern about defining the basic category classes (eg, <i>SimpleStatement</i> and <i>ComponentStatement</i>) and the specialized classes (eg, <i>Patient</i> , <i>Activity</i> , etc) as sibling classes under the <i>Statement</i> class since they represent different types of classifications of CEMs. An alternative solution could be to create two parent classes under the <i>Statement</i> class to separate the two groups of classes
Definition of classes (semantic)	5	The reviewers agreed that the semantic definition of each class is correct
Semantic relations (object property definitions)	5	The reviewers agreed that the domain and range defined for each property are correct
Context and application (<i>validation of the usage of the CEM-OWL model in a detailed CEM</i>)		
Class usage	4	The reviewers agreed that defining each detailed CEM (eg, <i>BloodPressurePanel</i>) as a new class and a subclass of the category it belongs to (eg, <i>Panel</i>) is appropriate and semantically correct. There was a discussion about the option on defining each detailed CEM as an individual of the category class (eg, <i>BloodPressurePanel</i> <i>rdf:type</i> <i>Panel</i>). The reviewers agreed that the current way is more appropriately aligned to the three-layer approach used for this representation
Relation usage	5	The reviewers agreed that the relations defined in the meta-ontology are sufficient to represent the connection between components in the detailed CEM
Cardinality constraints	5	The reviewers agreed that the cardinality constraints are defined correctly and the OWL cardinality constraints are sufficient to represent CEM cardinality constraints

DISCUSSION

Clinical information models harmonization

One of the important implications from our present work is that using OWL semantics to represent a CDL logical model would potentially facilitate accurate transformation of the CEMs specified in CDL into the format of ADL,⁸ which is a formal language for expressing archetypes. The HL7 Template Architecture standard discusses the semantic mappings between ADL and OWL. Some preliminary investigations have been undertaken to convert the ADL-based model into OWL. For instance, Lezcano *et al*¹⁵ developed an approach to translate definitions expressed in the openEHR ADL to a formal representation expressed using OWL, targeted at facilitating semantic interoperability for the computerized support of alerts, workflow management, and evidence-based healthcare across heterogeneous EHR systems. Martinez-Costa *et al* represented OpenEHR archetypes using OWL for the purpose of consistency checking. Notably, a recent international collaboration—the Clinical Information Modeling Initiative (CIMI)—committed to use ADL for their Clinical Information Model specifications.²⁵ OWL is also a CIMI recommended output for its final integrated clinical information model. In order to reuse CDL-based CEMs in the CIMI community, there will be a need to convert the CEMs in CDL into the format of ADL. Since both CDL and ADL have been represented using OWL, OWL can serve as a common language to map CDL and ADL together. We are currently investigating the ADL and CDL transformation based on their OWL rendering.²⁶

Semantic definition limitations

In the OWL representation, we tried to capture the semantic definitions of each CEM category. Some of the definitions, however, are difficult to represent in the OWL DL environment. For example, whether a clinical element should be defined as a collection or a panel depends on whether or not the associated elements are strongly semantically related. Unless the ‘strongly semantically related’ elements are defined in a domain ontology or information model, it is difficult for a computer system to automatically make the distinction. In addition, the CDL specification contains a restriction that specifies that the statements and/or associations within a panel cannot be modified independently. This kind of rule is better handled by downstream auditing tooling than by the semantic definition in OWL.

Property definitions

There are multiple ways to define relationships between two detailed clinical elements. One option is to use the properties defined in the meta-ontology (eg, *item*, *qual*, *mod*, *att*) to declare the relationships between two detailed clinical elements. For example, we can declare

```
BloodPressurePanel
```

```
item max 1
```

```
DiastolicBloodPressure
```

for the relation between the *BloodPressurePanel* and the *DiastolicBloodPressure*.

Another option is to define new properties for each pair of relations. For example, we can define a new property *diastolicBloodPressureMeas* to be a sub-property of the *item* property and declare the above relation as:

```
BloodPressurePanel diastolicBloodPressureMeas max 1
```

```
DiastolicBloodPressure
```

The latter approach will introduce a lot more properties, which could potentially lead to interoperability issues. But it

will be more straightforward to human users to understand the data representation. The first approach is usually preferred when the data are majorly used to automatic computation whereas the second approach is preferred when the data need to be processed manually.

CONCLUSION AND FUTURE WORK

In this paper, we introduce our efforts to represent the CEM in the OWL. We believe that the OWL representation of the CEM can be beneficial for the following reasons: (1) it lends formal semantic definitions to the CEM specifications; (2) it connects the CEM with various Semantic Web technologies to add authoring, reasoning, and querying capacities to the contents of the CEM; (3) it provides a unified platform to connect the CEM as an information model with different terminologies; and (4) it enables the harmonization of CEM models with clinical models that are represented in other languages such as ADL.

Several directions remain to be pursued. We will work on representing the HL7-based data types used by the CEM using both OWL 1.1 and the new OWL 2.0 data range definition features. Moreover, we plan to investigate the alignment between ADL and CDL to facilitate automatic transformation from detailed CEM models to ADL representation. Our ultimate goal is to represent patient instances in RDF and develop applications on top of this data to leverage the reasoning and storage mechanisms of Semantic Web technologies.

Acknowledgements We thank Ms. Teresa Conway, RN, MS, and Mr Feichen Shen for their help on evaluating the CEM-OWL representation.

Funding This work was made possible by funding from the Strategic Health IT Advanced Research Projects (SHARP) Program (90TR002) administered by the Office of the National Coordinator for Health Information Technology. The contents of the manuscript are solely the responsibility of the authors.

Contributors CT designed the CEM-OWL model, led the study design and analysis, and drafted the manuscript. GJ, TAO, RRF, and QZ contributed to the evaluation of the model. RRF, GJ, and JP helped draft the manuscript. DS helped with coding the CEM-OWL convertor. SMH and CGC provided institutional support and manuscript editing.

Patient consent Obtained.

Provenance and peer review Not commissioned; externally peer reviewed.

REFERENCES

- James A. Qualibria Constraint Definition Language (CDL), language guide 2010. Oct. 22, 2010.
- GE/Intermountain Clinical Element Model Search. (cited 2012). <http://www.clinicalelement.com/>. (accessed 22 Nov 2012).
- Rea S, Pathak J, Savova G, *et al*. Building a robust, scalable and standards-driven infrastructure for secondary use of EHR data: The SHARPN project. *J Biomed Inform* 2012;45:763–71.
- Steiner DJ, Coyle JF, Rocha BH, *et al*. Medical data abstractionism: fitting an EMR to radically evolving medical information systems. *Stud Health Technol Inform* 2004;107(Pt 1):550–4.
- OWL Web Ontology Language Reference. (cited 2012). <http://www.w3.org/TR/owl-ref/> (accessed 22 Nov 2012)
- Horrocks I, Patel-Schneider PF, McGuinness DL, *et al*. *OWL: a description logic based ontology language for the semantic web. The description logic handbook: theory, implementation, and applications*. 2nd edn. Cambridge University Press, 2007.
- Rule Interchange Format (RIF). <http://www.w3.org/standards/techs/rif> (accessed 22 Nov 2012)
- HL7 Template and Archetype Architecture. (02/23/2012). http://www.hl7.org/library/committees/template/HL7_Atlanta_10_20_04.doc (accessed 22 Nov 2012)
- Donnelly K. SNOMED-CT: the advanced terminology and coding system for eHealth. *Stud Health Technol Inform* 2006;121:279–90.
- <https://www.nlm.nih.gov/research/umls/rxnorm/> (accessed 22 Nov 2012)
- Rector AL. The interface between information, terminology, and inference models. *Stud Health Technol Inform* 2001;84(Pt 1):246–50.
- Santos MR, Bax MP, Kalra D. Building a logical EHR architecture based on ISO 13606 standard and semantic web technologies. *Stud Health Technol Inform* 2010;160(Pt 1):161–5.

- 13 Martinez-Costa C, Menarguez-Tortosa M, Fernandez-Breis JT, et al. A model-driven approach for representing clinical archetypes for Semantic Web environments. *J Biomed Inform* 2009;42:150–64.
- 14 Tao C, Jiang G, Wei W, et al. Towards semantic-web based representation and harmonization of standard meta-data models for clinical studies. *AMIA Summits Transl Sci Proc* 2011;2011:59–63.
- 15 Lezcano L, Sicilia MA, Rodriguez-Solano C. Integrating reasoning and clinical archetypes using OWL ontologies and SWRL rules. *J Biomed Inform* 2011;44:343–53.
- 16 Heymans S, McKennirey M, Phillips J. Semantic validation of the use of SNOMED CT in HL7 clinical documents. *J Biomed Semantics* 2011;2:2.
- 17 Resource description framework (rdf) (02/23/2012). <http://www.w3.org/RDF/> (accessed 22 Nov 2012)
- 18 Tao C, Parker CG, Oniki TA, et al. An OWL meta-ontology for representing the clinical element model. *American Medical Informatics Association Annual Symposium*; 2011.
- 19 Drummond N, Rector A, Stevens R, et al., eds. *Putting OWL in order: patterns for sequences in OWL. OWL experiences and directions (OWLEd 2006)*. Athens, GA, 2006.
- 20 Representing Specified Values in OWL: “value partitions” and “value sets”. <http://www.w3.org/TR/swbp-specified-values/> (accessed 22 Nov 2012)
- 21 Measurement Units Ontology. http://forge.morfeo-project.org/wiki_en/index.php/Units_of_measurement_ontology (accessed 22 Nov 2012)
- 22 The Unified Code for Units of Measure. (cited 2012). <http://www.unitsofmeasure.org/> (accessed 22 Nov 2012)
- 23 Tao C, Wei WQ, Solbrig HR, et al. CNTRO: a semantic web ontology for temporal relation inferencing in clinical narratives. *AMIA Annu Symp Proc* 2010;2010:787–91.
- 24 Brank J, Grobelnik M, Mladenić D. A survey of ontology evaluation techniques. *Proc of 8th Int multi-conf Information Society* 2005: 166–9.
- 25 The CIMI wiki: http://informatics.mayo.edu/CIMI/index.php/Main_Page (accessed 22 Nov 2012)
- 26 Legaz-García MC, Tao C, Menárguez-Tortosa M, et al. An approach for the mapping of CEM and ppenEHR archetypes. *AMIA Clinical Research Informatics Summit*; 2013, submitted.